estimated from the 1980 and 1990 U.S. censuses. There were 525 identified deaths. All except two decedents were male, and the majority were Caucasian (79.2%). The mean age of decedents was 39 years. Death rates were higher among older workers. The crude fatality rate for the overall study period was 15.4 per 100,000 worker-years, with higher rates found among African-Americans (22.9) than among Caucasians (14.5). Occupations within the industry with the highest rates were laborers (49.5), truck drivers (43.2), operating engineers (37.2), roofers (32.8), and electricians (29.0). Falls (26.7%), electrocutions (20.4%), and motor vehicle accidents (18.9%) were found to be the leading causes of death. These findings suggest a need for continued attention to the hazards of heights and electric currents and a need for occupational safety standards for motor vehicles. This study also suggests that the hazards facing construction laborers require further investigation.

Kazan, E. and M. A. Usmen (2018). "Worker safety and injury severity analysis of earthmoving equipment accidents." J Safety Res 65: 73-81.

INTRODUCTION: Research on construction worker safety associated with construction equipment has mostly focused on accident type rather than injury severity and the embedded factor relationships. Significant variables and their effects on the degree of injury are examined for earthmoving equipment using data from OSHA. Four types of equipment, backhoe, bulldozer, excavator, and scraper are included in the study. Accidents involving on-foot workers and equipment operators are investigated collectively, as well as separately. METHODS: Cross tabulation analysis was conducted to establish the associations between selected categorical variables, using degree of injury as a dichotomous dependent variable (fatal vs. nonfatal) and a number of independent variables having differe (o)-4 (r)-1 (dl]TJ0 u)-1 (ha)4 Nisat moswerecacated tatemi(:)-6ho2 (w)1 (m)-u3 (c)4 a dlerala anatlative iala5ofiv annd erato. r(f)12 (S)-Ud tTS:l w aserabu andat (o)-4 6at welvepariabl as w (ovi)-2 (ı

4 (s)-2 (e)3 (a)4 (t)-bnd etnt mafat mvib7 (a) (oc)k ona

Perspectives on nail gun safety were sought from residential contractors as part of an injury surveillance and prevention effort (2005-2008). Anonymous surveys inquired about tool use, training, injury risk, and awareness of the 2003 American National Standards Institute (ANSI) standard calling for shipment of pneumatic nail guns used in wood framing with sequential actuation. Despite some awareness of inexperience, lack of training, speed and tool design in injury causation, 55 percent consistently reported injuries resulted from worker carelessness. Contractors reported safety experiences of their employees were considerably better than those of other residential contractors. After five years, only 16 percent reported any awareness of the voluntary standard. These findings raise questions as to what gains can realistically be expected from passage of voluntary standards such as the one described here. Given that the epidemiology of acute injuries from pneumatic nail guns is now well-described, the safer sequential trigger should be required to protect workers.

Lipscomb, H. J., et al. (2015). "Musculoskeletal concerns do not justify failure to use safer sequential trigger to prevent acute nail gun injuries." Am J Ind Med 58(4): 422-427.

Background: Acute nail gun injuries can be controlled significantly by using tools with sequential triggers and training. Concern has been raised that sequential triggers, which require that the nose piece of the gun be depressed prior to pulling the trigger, could increase risk of musculoskeletal problems. Methods: We conducted active injury surveillance among union carpenter apprentices to monitor acute injuries and musculoskeletal disorders between 2010 and 2013. Results: Acute injury risk was 70% higher with contact trip rather than sequential triggers. Musculoskeletal risk was comparable (contact trip 0.09/10,000hr (95% CI, 0.02-0.26); sequential 0.08/ 10,000hr (95% CI 0.02-0.23)). Conclusions: Concern about excess risk of musculoskeletal problems from nail guns with sequential triggers is unwarranted. Both actuation systems carry comparable musculoskeletal risk which is far less than the risk of acute injury; there is clearly no justification for failure to prevent acute injuries through use of the safer sequential trigger. Am. J. Ind. Med. 58:422-427, 2015. © 2015 Wiley Periodicals, Inc.

Lipscomb, H. J., et al. (2008). "Prevention of traumatic nail gun injuries in apprentice carpenters: use of population-based measures to monitor intervention effectiveness." Am J Ind Med 51(10): 719-727.

INTRODUCTION: Nail guns are responsible for a significant injury burden in residential construction. Risk, based on hours of work, is particularly high among apprentice carpenters due in part to more frequent exposure to tool use. METHODS: Nail gun injuries were evaluated over 3 years among carpenters enrolled in two apprenticeship programs in the Midwest (2.3 million residential work hours observed) following initiation of training and a voluntary ANSI standard change calling for safer sequential triggers on framing nailers. Injury rates, based on hours of tool use, were calculated yearly. Rates and adjusted rate ratios were calculated with Poisson regression. Attributable risk percent (AR%) and population attributable risk (PAR%) were calculated yearly for modifiable independent risk factors for injury including lack of training in tool use and type of trigger mechanism on tools being used. RESULTS: As apprentices received training and safer trigger mechanisms became more widespread, injury rates decreased significantly (31%). While school training and hands-on mentoring were both important, injury rates were lowest among apprentices who received both. Although injury rates changed over the observation period, the relative risk comparing trigger mechanisms did not; contact trip triggers consistently carried a twofold risk. CONCLUSIONS: Although training and safer trigger use both increased, because of the relative prevalence of training and trigger exposures in this population, the engineering solution consistently

conditions. Mean differences in time required, nails used, and proper placement were evaluated considering the trigger used and whether the building was the carpenter's first or second project. RESULTS: The sequential trigger tool required a mean of 10 additional minutes of active nailing time, which represented 10% of mean nailing time (97 minutes) but only 0.77% of the total mean work time (1,298 minutes) to construct each shed. No significant differences were observed in nail count or placement. The majority of the time variability was related to who was using the tool, rather than the type of tool in the person's hand. CONCLUSIONS: Productivity concerns3,S
orrnd Heool in ton's .1 usionsideron>1TJT*(e)4 (s).

prevent traumatic injuries resulting from a worker coming into contact with objects or equipment. METHOD: This descriptive study of work-related contact injuries in the construction industry that were treated in emergency departments (EDs) between 1998 and 2005 utilized records of work injuries captured through a national probability-based sample of U.S. hospitals with 24-hour ED services. RESULTS: Contact injuries accounted for 54% of all construction ED-treated injuries. Hospitalizations were most common for injuries from contact with discharged nails from pneumatic nail guns, with hand held power saws, and fixed saws. Some injuries were proportionally more serious and sometimes involved multiple workers including trenching injuries and those resulting from collapse of buildings under construction, walls, roofs, and scaffolding. DISCUSSION AND IMPACT: Given that nail gun use is limited primarily to wood frame construction, efforts are needed to control frequent serious injuries associated with these tools. Enforcement of existing trenching regulations is also needed.

Lipscomb, H. J., et al. (2010). "Nonfatal tool- or equipment-related injuries treated in US emergency departments among workers in the construction industry, 1998-2005." Am J Ind Med 53(6): 581-587.

BACKGROUND: Individuals in the construction industry are exposed to a variety of tools and pieces of equipment as they work. METHODS: Data from the National Institute for Occupational Safety and Health (NIOSH) occupational supplement to the National Electronic Injury Surveillance System (NEISS-Work) were used to characterize tool- and equipment-related injuries among workers in the construction industry that were treated in US emergency departments between 1998 and 2005. Based on a national stratified probability sample of US hospitals with 24 hr emergency services, NEISS-Work allows calculation of national injury estimates. RESULTS: Over the 8-year period between 1998 and 2005, we estimated 786,900 (95% CI 546,600-1,027,200) ED-treated tool- or equipment-related injuries identified by the primary or secondary source of injury code. These injuries accouu-6ab8 (u)-4 (raf)3 (i)-2 (nj)-2 (ura4 (o)-5 (a)-10 9)-10CiBK Turbs0.004 Hi (ct)-6 (l

welders. Subjects were mainly male (97.1%) and from manufacturing (70.4%), service (11.8%), or construction (8.4%) related industries. Most injuries were foreign body (71.7%) or burn (22.2%) and 17.6% were bilateral. Common activities include welding (31.9%) and/or grinding (22.5%). Being struck by an airborne object occurred in 56.3% of cases. Non-

to worker health, especially among men in jobs requiring intensive manual labour. Evidence showed that increased legislative regulation led to a decline in eye injuries, which was consistent with other recent findings in the area. Additionally, targeting groups most at risk, increasing worker training, providing effective eye protection equipment, and developing workplace safety cultures may together reduce occupational eye injuries.

McCann, M. (2006). "Heavy equipment and truck-related deaths on excavation work sites." J Safety Res 37(5): 511-517.

PROBLEM: Contact with objects and equipment is the third leading cause of death in construction. This study examines heavy equipment- and truck-related deaths in the excavation work industry in construction. METHODS: The Bureau of Labor Statistics Census of Fatal Occupational Injuries identified 253 heavy equipment related deaths on construction sites in the Excavation Work industry for the years 1992-2002. RESULTS: Heavy equipment operators and construction laborers made up 63% of the heavy equipment- and truck-related deaths. Backhoes and trucks were involved (vy (g(up f)3 (or)3 ( )-10 w)2 (or)-7 (ve)4 (r)3 ("(t)- (on f)3 (ont)-2 5))3 ,(a)4 (ndb)-10 (e)4 (vy (g(sr)-11 (t) -and trucks ck-

analysis reveals 10 important features and shows that four of these features are significantly associated with higher probabilities of roadside work zone collisions.

Odeh, I., et al. (2009). "Field experiments to evaluate and control light tower glare in nighttime work zones." Journal of Construction Engineering and Management 135(9): 911-919.

An increasing volume of highway repair and construction work is being performed during the off-peak nighttime hours to mitigate the impact of construction-related daytime traffic congestions and shorten the duration of construction operations. The utilization and placement of light towers to illuminate the work zone in this type of construction can cause harmful levels of glare for both drivers and construction workers. This paper presents the results of field experiments which were conducted to (1) study the levels of glare and lighting performance generated by light towers in and around nighttime work zones; (2) analyze the combined impact of the light tower set up parameters including its height as well as its aiming and rotation angles on glare and lighting performance; and (3) provide practical recommendations to reduce and control lighting glare in and around nighttime work zones. The results of these experiments confirm that the set up of light towers has a significant impact on glare and therefore it should be carefully designed and executed on nighttime highway

o 3] T J - 0 . 0 0 1 - 2 (

Plog, B., et al. (2006). "Strategies to Prevent Trenching-Related Injuries and Deaths (CPWR Report)."

Prahlow, J. A., et al. (2020). "Elevator-Related Deaths." J Forensic Sci 65(3): 823-832.

Elevators are mechanical transportation devices used to move vertically between different levels of a building. When first developed, elevators lacked the safety features. When safety mechanisms were developed, elevators became a common feature of multistory buildings. Despite their well-regarded safety record, elevators are not without the po (ll)]TJ0 5 TD (i)-2 (s)-1(l)-2 (. ((e)4 (s)-1 d(

three different pieces of construction equipment and multiple operators are presented. The developed method has the potential in automatically determining the spaces around vehicles that are currently not in the field-of-view of the vehicle operator thus providing eventually additional means and technology for improving safety in construction. © 2011 Elsevier Ltd. All rights reserved.

Ray, S. J. and J. Teizer (2013). "Computing 3D blind spots of construction equipment: Implementation and evaluation of an automated measurement and visualization method utilizing range point cloud data." Automation in Construction 36: 95-107.

Limited visibility due to blind spots of construction equipment was responsible for 55% of the visibility-related fatalities in the construction industry. Knowledge of blind spot aids in improving safety on construction sites and the design of equipment cabin itself. Existing approaches for blind spot measurement that follow international standards typically require a time-consuming set-up and are limited by the number of different visibility analyses that can be performed. A new approach to compute blind spot in a fast and efficient way using point cloud data of equipment is presented. The developed approach allows performing different analyses such as: volumetric blind spots, blind spot map, 12 m circumference visibility, rectangular 1 m boundary visibility, and worker visibility. In addition, the above set of analyses can be performed from different viewpoints located virtually anywhere inside the equipment cabin. Validating against synthetic "noisy" point clouds, robustness and accuracy of the approach is established.

Sakhakarmi, S. and J. Park ((. r/%Tw [(nt)-2 ((e)4(. P)-4(nt)-2 ((e)4(. P)-4(z (e)4()4 (r)3 (m)-i)-2 (r)02 Tc -0

Shen, X., et al. (2016). "Hazardous Proximity Zone Design for Heavy Construction Excavation Equipment." Journal of Construction Engineering and Management 142(6): 05016001.

The construction industry continues to be among the leading industries for workplace fatalities in the United States. After experiencing 824 fatal injuries in 2013, the construction industry ranks as one of the most dangerous work environments when compared with other private industrial sectors in the United States. Conditions of construction sites often produce hazardous proximity situations by requiring pedestrian workers and heavy equipment to operate at close proximity. Injury and fatality statistics indicate that current safety practices of construction workers have proven inadequate. The research aims to design hazard zone around pieces of heavy construction equipment in which site personnel should not enter during construction operations. The scope is limited to construction sites and equipment at a horizontal grade and hazards between heavy construction excavation equipment and workers-on-foot. A framework for creating the hazard zone around a piece of construction equipment is presented including detailed methodology discussions for each step. A user interface is also presented that automatically creates a hazard zone around select pieces of construction equipment based on user-defined parameters. The hazard zone for a dump truck, excavator, and backhoe are shown using the created framework. Results indicate that hazard zones for pedestrian workers can be created around construction equipment to increase hazard awareness for workers. Contributions for this research include a user-friendly hazard zone creation tool and database for safety managers and scientific evaluation data of the created hazard zone framework. Safety standards can be formulated based on the design and implement hazard zones on equipment.

Shrestha, P. P., et al. (2018). "Types and factors affecting injury rates of mechanical contractors." Work 61(1): 135-148.

BACKGROUND: In the United States, about 38,000 cases of nonfatal workplace injuries were reported in 2015, in the category of 'mechanical work' (plumbing, heating, and air conditioning); this is nearly identical to the number of cases reported under 'building construction'. OBJECTIVE: This paper analyzes the types and rates of injuries and illnesses of mechanical contractors of southern Nevada, including the nature of the injuries and illnesses, body parts affected

most serious occupational hazards. Unlike most previous surveys of the field, this interdisciplinary literature search captured research published in the construction management and engineering literature as well as that in public health and medicine journals. The researchers found 741 articles by US-based lead authors, with falls the most-studied safety hazard (89 articles) and airborne silica exposure the most-studied health hazard (51), both among the deadliest current hazards in construction occupational safety and health, but much asbestos research was sponsored by companies involved in litigation, generating few findings useful for protecting today's workers. The review described important trends in the literature, including increased attention to noise and hearing loss, a growing number of intervention studies, and greater concern for populations at disproportionate risk (e.g., small/residential, Latino/immigrant, younger/older workers, & women working in construction). The National Institute for Occupational Safety and Health (NIOSH) directly or indirectly funded a majority of the published research. Policymakers should understand that most occupational safety and health research depends on NIOSH funding.

Sun, C., et al. (2012). "Safety evaluation of sequential warning lights in tapers at nighttime work zones." Transportation Research Record: 1-8.

Safety improvement at nighttime work zones is important because of visibility concerns after dark. The deployment of sequential lights is an innovative method to improve driver recognition of lane closures and work zone tapers. Sequential lights are wireless warning lights that flash in a sequence to delineate clearly the taper at work zones. The effectiveness of sequential lights was investigated with the use of controlled field studies. Traffic parameters were collected at the same field site with and without the deployment of sequential lights. Three surrogate performance measures (the speeds of approaching vehicles, the number of late taper merges, and the locations where vehicles merged into an open lane from a closed lane) were used to determine the impact of sequential lights on safety. The results of this study showed that sequential warning lights had a net positive effect: the warning lights reduced the speeds of approaching vehicles and enhanced driver

BACKGROUND: Although traumatic brain injury (TBI) is one of the leading causes of death

has the highest burden of occupational fatalities in the USA of all industries, and foreign-born Hispanic workers are disproportionately affected. Design/methodology/approach Data were obtained from 3,093 death certificates maintained by the Consulate General of Mexico in Atlanta, Georgia. Standardized mortality ratios (SMR) were used to compare occupational-related deaths among construction industry occupations, and logistic regression models were used to examine the relationship between manners of death not related to occupation and employment in the construction industry. Findings The proportion of Mexican immigrants who died from occupational injuries is higher among all construction workers (SMR = 1.31), roofers (SMR = 2.32) and carpenters (SMR = 2.25) than other workers. Among the population in this analysis suicide [adjusted odds ratio (aOR) = 0.63] and death from natural causes (aOR = 0.70) were inversely related to work in the construction industry. Research limitations/implications Interventions to reduce occupational fatalities among Mexican migrant construction workers should target roofers and carpenters. Future research should further investigate the industry's association with suicide and natural death. Originality/value This is one of the first analyzes that investigated associations between construction industry employment and non-occupational fatalities among immigrants. The analysis provides evidence that a large portion of the Mexican immigrant population is used in the construction industry (38%) and face elevated risks for occupational fatalities and the results of this investigation should encourage greater surveillance of occupational illness and injury among foreign-born immigrants who work in construction, as well as other high-risk industries.

Yadav, N., et al. (2022). "On-Body Placement of Wearable Safety Promotion Devices Based on Wireless Communication for Construction Workers-on-Foot: State-of-the-Art Review." Sensors (Basel) 22(9).

High auditory noise levels and limited visibility are often considered among the main factors that hinder seamless communication on construction sites. Many previous research studies have

orc 0.02

on-

Topics in Construction Safety and Health:

vehicle speed. The researchers used fixed-